


Detailed Specifications & Technical Data



1243A2 Paired - DataTwist® 3 UTP Cable

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Color Code Chart : No. 5 for Paired Cables (Western Electric Standard).pdf</p>
---	--

Description:

24 AWG solid bare copper conductors, twisted pairs, low-smoke PVC insulation, low-smoke PVC jacket. Sequential marking at two foot intervals.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	2
Total Number of Conductors	4
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	LS PVC - Low Smoke Polyvinylchloride
---------------------	--------------------------------------

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue & Blue	2	White/Orange & Orange

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material Trade Name	Flamarrest®
Outer Jacket Material	LS PVC - Low Smoke Polyvinyl Chloride
Outer Jacket Ripcord	No

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.170 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
-----------------------------	----------------

Detailed Specifications & Technical Data



1243A2 Paired - DataTwist® 3 UTP Cable

Bulk Cable Weight	12 lbs/1000 ft.
Max. Recommended Pulling Tension	13 lbs.
Min. Bend Radius (Install)	1.6 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMP, UL444
IEEE Specification	802.3 10BaseT, 100BaseT4
TIA/EIA Specification	568-B.2 Category 3
Other Specification	NEMA WC-63 Category 3, UL verified to TIA/EIA-568-B.2, Category 3.

FLAME TEST:

UL Flame Test	UL910 Steiner Tunnel
CSA Flame Test	FT6

PLENUM/NON-PLENUM:

Plenum (Y/N)	Y
Non-Plenum Number	1227A1

ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz	19 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	330 pF/100 m
Nominal Velocity of Propagation	61 %
Nominal Delay	1.5 ns/ft
Maximum Conductor DC Resistance @ 20 Deg. C	9.38 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	5 %
Max. Operating Voltage - UL	300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals :

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. Structural Return Loss (dB)	Fitted Impedance (Ohms)
1	2.56	41.0	No Spec	12.0	100 ± 15%
4	5.58	32.0	No Spec	12.0	100 ± 15%
10	9.71	26.	No Spec	12.00	100 ± 15%
16	13.10	23	No Spec	9.96	100 ± 15%

NOTES:

Notes	Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 3.
-------	---

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
------	-------------	--------------	--------------------	--------------	-------

**Detailed Specifications &
Technical Data**



1243A2 Paired - DataTwist® 3 UTP Cable

1243A2 009U1000	2 PR #24 FLRST FLRST	U1000	14	WHITE	
-----------------	-------------------------	-------	----	-------	--

Revision Number: 1 Revision Date: 09-09-2004

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.