


**Detailed Specifications & Technical Data**



**1700A Paired - DataTwist® Enhanced Category 5e**

	<p><b>For more information please call</b>  <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p> <p><b>Color Code Chart : No. 8 for DataTwist Cables (Modified Western Electric).pdf</b></p>
---	---

**Description:**

4 Pair UTP, 350MHz Enhanced Category 5e, Vertical Tray Rated, 24 AWG Solid Bare Copper, Polyolefin Insulation, Bonded Pairs, PVC Jacket, Rip Cord, Sequential Marking at Two Foot Intervals

**SUITABLE APPLICATIONS:**

Suitable Applications	Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422, Noisy Environments   US Patent #'s 5, 606, 151; 5, 734, 126
-----------------------	---

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

**INSULATION:**

Insulation Material	PO - Polyolefin
---------------------	-----------------

**Pair Color Code Chart :**

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

**OUTER SHIELD:**

Outer Shield Material	Unshielded
-----------------------	------------

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Ripcord	Yes

**OVERALL NOMINAL DIAMETER:**

**Detailed Specifications &  
Technical Data**



**1700A Paired - DataTwist® Enhanced Category 5e**

Overall Nominal Diameter	0.200 in.
--------------------------	-----------

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range	-20°C To +80°C
Bulk Cable Weight	29 lbs/1000 ft.
Max. Recommended Pulling Tension	40 lbs.
Min. Bend Radius (Install)	0.25 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

NEC/(UL) Specification	CM, UL444
CEC/C(UL) Specification	CM
IEC Specification	11801 Category 5
TIA/EIA Specification	568-B.2 Category 5e
Other Specification	NEMA WC-63.1 Category 5e, UL Verified to Category 5e

**FLAME TEST:**

UL Flame Test	UL1581 Vertical Tray
CSA Flame Test	FT1

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	N
Plenum Number	1701A

**ELECTRICAL CHARACTERISTICS:**

Nom. Mutual Capacitance @ 1 KHz	15 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	66 pF/100 m
Nominal Velocity of Propagation	70 %
Maximum Delay (ns/100 m)	510 ns/100 m
Maximum Delay Skew (ns/100m)	25 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	3 %
Max. Operating Voltage - UL	300 V RMS

**ELECTRICAL CHARACTERISTICS - PREMISE:**

Premise Cable Electricals Table 1 :	
-------------------------------------	--

**Detailed Specifications &  
Technical Data**



**1700A Paired - DataTwist® Enhanced Category 5e**

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2.0	65.3	65.3	63.3	63.3	20.0	
4	4.0	56.3	56.3	52.3	52.3	23.0	
8	5.7	51.8	51.8	46.1	46.1	24.5	
10	6.4	50.3	50.3	43.9	43.9	25.0	
16	8.1	47.3	47.3	39.1	39.1	25.0	
20	9.2	45.8	45.8	35.2	35.2	25.0	
25	10.3	44.3	44.3	34.1	34.1	24.3	
31.25	11.6	42.9	42.9	31.3	31.3	23.6	
62.5	16.8	38.4	38.4	21.6	21.6	21.5	
100	21.7	35.3	35.3	17.1	17.1	20.1	
155	27.7	32.5	32.5	4.7	4.7	19.0	
200	32.0	30.8	30.8	3.0	3.0	19.0	
250	36.4	29.3	29.3	>0	>0	18.0	
300	40.5	28.2	28.2			18.0	
310	41.3	27.9	27.9			18.0	
350	44.3	27.2	27.2			17.0	

Premise Cable Electricals Table 2 :

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 12	105 ± 10	63.8	60.8
4	100 ± 12	100 ± 10	51.7	48.7
8	100 ± 12	100 ± 10	45.7	42.7
10	100 ± 12	100 ± 10	43.8	40.8
16	100 ± 12	100 ± 10	39.7	36.7
20	100 ± 12	100 ± 10	37.7	34.7
25	100 ± 15	100 ± 10	35.8	32.8
31.25	100 ± 15	100 ± 10	33.9	30.9
62.5	100 ± 15	100 ± 10	27.8	24.8
100	100 ± 15	100 ± 10	23.8	20.8
155	100 ± 18	100 ± 10	19.9	16.9
200	100 ± 18	100 ± 10	17.7	14.7
250	100 ± 20	100 ± 10	15.8	12.8
300	100 ± 20	100 ± 10	14.2	11.2
310	100 ± 20	100 ± 10	13.9	10.9
350	100 ± 22	100 ± 10	12.9	9.9

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1700A 0021000	4 PR #24 DATATWIST FR PVC	1000	22	RED	C

**Detailed Specifications &  
Technical Data**



**1700A Paired - DataTwist® Enhanced Category 5e**

1700A 0023000	4 PR #24 DATATWIST FR PVC	3000	63	RED	C
1700A 002U1000	4 PR #24 DATATWIST FR PVC	U1000	22	RED	
1700A 0031000	4 PR #24 DATATWIST FR PVC	1000	22	ORANGE	C
1700A 003U1000	4 PR #24 DATATWIST FR PVC	U1000	22	ORANGE	
1700A 0041000	4 PR #24 DATATWIST FR PVC	1000	22	YELLOW	C
1700A 004U1000	4 PR #24 DATATWIST FR PVC	U1000	22	YELLOW	
1700A 0051000	4 PR #24 DATATWIST FR PVC	1000	22	GREEN, DARK	C
1700A 005U1000	4 PR #24 DATATWIST FR PVC	U1000	22	GREEN, DARK	
1700A 0061000	4 PR #24 DATATWIST FR PVC	1000	22	BLUE, LIGHT	C
1700A 0061640	4 PR #24 DATATWIST FR PVC	1640	36.08	BLUE, LIGHT	C
1700A 0063000	4 PR #24 DATATWIST FR PVC	3000	63	BLUE, LIGHT	C
1700A 006U1000	4 PR #24 DATATWIST FR PVC	U1000	22	BLUE, LIGHT	
1700A 008U1000	4 PR #24 DATATWIST FR PVC	U1000	22	GRAY	
1700A 0091000	4 PR #24 DATATWIST FR PVC	1000	22	WHITE	C
1700A 0093000	4 PR #24 DATATWIST FR PVC	3000	63	WHITE	C
1700A 009U1000	4 PR #24 DATATWIST FR PVC	U1000	22	WHITE	C
1700A 0101000	4 PR #24 DATATWIST FR PVC	1000	22	BLACK	C
1700A 010U1000	4 PR #24 DATATWIST FR PVC	U1000	22	BLACK	
1700A B021000	4 PR #24 DATATWIST FR PVC	1000	22	PURPLE	C

**Detailed Specifications &  
Technical Data**



**1700A Paired - DataTwist® Enhanced Category 5e**

1700A B02U1000	4 PR #24 DATATWIST FR PVC	U1000	22	PURPLE	
1700A F2V1000	4 PR #24 DATATWIST FR PVC	1000	22	GRAY, DEC	C
1700A F2V1640	4 PR #24 DATATWIST FR PVC	1640	36.08	GRAY, DEC	C
1700A F2V3000	4 PR #24 DATATWIST FR PVC	3000	63	GRAY, DEC	C
1700A F2V3280	4 PR #24 DATATWIST FR PVC	3280	72.16	GRAY, DEC	C
1700A F2VU1000	4 PR #24 DATATWIST FR PVC	U1000	22	GRAY, DEC	

C = CRATE REEL PUT-UP.

Revision Number: 1      Revision Date: 07-22-2004

© 2003 Belden Wire & Cable Company  
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.