

Detailed Specifications & Technical Data



1700S6 Paired - DataTwist® 350 Enhanced Category 5e

 <p style="font-size: 2em; margin-top: 20px;">DataTwist 350</p>	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Color Code Chart : No. 8 for DataTwist Cables (Modified Western Electric).pdf</p>
--	--

Description:

Banana Peel® 6 component, 4 pair UTP, riser rated, 24 AWG solid bare copper conductors, polyolefin insulation, bonded pairs, PVC jacket, rip cord. Sequential marking at two foot intervals.

SUITABLE APPLICATIONS:

Suitable Applications	Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422, Noisy Environments, 350MHz Enhanced Category 5e
-----------------------	---

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	24
Total Number of Conductors	48
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PO - Polyolefin
---------------------	-----------------

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

INNER JACKET:

Inner Jacket Material	PVC - Polyvinyl Chloride
Inner Jacket Diameter	.204 in.

OVERALL CABLING:

Overall Cabling Fillers	Spline
-------------------------	--------

OUTER SHIELD:

Detailed Specifications & Technical Data



1700S6 Paired - DataTwist® 350 Enhanced Category 5e

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	Unjacketed
-----------------------	------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.600 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +80°C
Bulk Cable Weight	139 lbs/1000 ft.
Max. Recommended Pulling Tension	1440 lbs.
Min. Bend Radius (Install)	0.6 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR
CEC/C(UL) Specification	CMG
IEC Specification	Individual leg: 11801 Category 5
TIA/EIA Specification	Individual leg: ANSI/TIA/EIA-568-B.2 Category 5e
Other Specification	Individual leg: NEMA WC-63.1 Category 5e, UL Verified to Category 5e

FLAME TEST:

UL Flame Test	UL1666 Riser
CSA Flame Test	FT4

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	1701S6

ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz	15 pF/ft
Maximum Capacitance Unbalance (pF/100 m)	66 pF/100 m
Nominal Velocity of Propagation	70 %
Maximum Delay (ns/100 m)	510 ns/100 m
Maximum Delay Skew (ns/100m)	25 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	3 %
Max. Operating Voltage - UL	300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals Table 1 :	
-------------------------------------	--

Detailed Specifications & Technical Data



1700S6 Paired - DataTwist® 350 Enhanced Category 5e

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2.0	65.3	65.3	63.3	63.3	20.0	
4	4.0	56.3	56.3	52.3	52.3	23.0	
8	5.7	51.8	51.8	46.1	46.1	24.5	
10	6.4	50.3	50.3	43.9	43.9	25.0	
16	8.1	47.3	47.3	39.1	39.1	25.0	
20	9.2	45.8	45.8	35.2	35.2	25.0	
25	10.3	44.3	44.3	34.1	34.1	24.3	
31.25	11.6	42.9	42.9	31.3	31.3	23.6	
62.5	16.8	38.4	38.4	21.6	21.6	21.5	
100	21.7	35.3	35.3	17.1	17.1	20.1	
155	27.7	32.5	32.5	4.7	4.7	19.0	
200	32.0	30.8	30.8	3.0	3.0	19.0	
250	36.4	29.3	29.3	>0	>0	18.0	
300	40.5	28.2	28.2			18.0	
310	41.3	27.9	27.9			18.0	
350	44.3	27.2	27.2			17.0	

Premise Cable Electricals Table 2 :

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 12	105 ± 10	63.8	60.8
4	100 ± 12	100 ± 10	51.7	48.7
8	100 ± 12	100 ± 10	45.7	42.7
10	100 ± 12	100 ± 10	43.8	40.8
16	100 ± 12	100 ± 10	39.7	36.7
20	100 ± 12	100 ± 10	37.7	34.7
25	100 ± 15	100 ± 10	35.8	32.8
31.25	100 ± 15	100 ± 10	33.9	30.9
62.5	100 ± 15	100 ± 10	27.8	24.8
100	100 ± 15	100 ± 10	23.8	20.8
155	100 ± 18	100 ± 10	19.9	16.9
200	100 ± 20	100 ± 10	17.7	14.7
250	100 ± 20	100 ± 10	15.8	12.8
300	100 ± 20	100 ± 10	14.2	11.2
310	100 ± 20	100 ± 10	13.9	10.9
350	100 ± 22	100 ± 10	12.9	9.9

NOTES:

Notes US Patent #'s 5, 606, 151; 5, 734, 126; Banana Peel® Patent Pending.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
------	-------------	--------------	--------------------	--------------	-------

**Detailed Specifications &
Technical Data**



1700S6 Paired - DataTwist® 350 Enhanced Category 5e

1700S6 0061000	BONDED FILLER COMPOSITE	1000	149	BLUE, LIGHT	C
1700S6 006500	BONDED FILLER COMPOSITE	500	77.5	BLUE, LIGHT	C
1700S6 F2V1000	BONDED FILLER COMPOSITE	1000	149	GRAY, DEC	C
1700S6 F2V500	BONDED FILLER COMPOSITE	500	77.5	GRAY, DEC	C

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 06-18-2004

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.