

**Detailed Specifications &
Technical Data**



5202UP Non-Paired - New Generation®

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--

Description:

Bare high-conductivity ETP copper conductors, highly stranded for ultra flexibility, high-grade PVC insulation, PVC jacket with ripcord. Sequential footage marking every two feet.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	4
Total Number of Conductors	4
AWG	16
Stranding	65
Conductor Material	Bare High-Conductivity ETP Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.015 in.

OVERALL CABLING:

Overall Cabling Lay Length	3.00 in.
Overall Cabling Twists/ft.	4
Overall Cabling Color Code Chart	Black, White, Red, Green

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.015 in.
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.244 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
UL Temperature Rating	75°C

**Detailed Specifications &
Technical Data**



5202UP Non-Paired - New Generation®

Bulk Cable Weight	48 lbs/1000 ft.
Max. Recommended Pulling Tension	130 lbs.
Min. Bend Radius (Install)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
------------------------	----

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
---------------	----------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Inductance	0.16 μ H/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	30 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	4.05 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	15.5 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
5202UP 0051000	4 #16 PVC FRPVC	1000	51	GREEN, DARK	
5202UP 005500	4 #16 PVC FRPVC	500	27	GREEN, DARK	
5202UP 005U1000	4 #16 PVC FRPVC	U1000	51	GREEN, DARK	
5202UP 005U500	4 #16 PVC FRPVC	U500	40	GREEN, DARK	
5202UP 0081000	4 #16 PVC FRPVC	1000	51	GRAY	C
5202UP 008500	4 #16 PVC FRPVC	500	27	GRAY	
5202UP 008U1000	4 #16 PVC FRPVC	U1000	51	GRAY	
5202UP 008U500	4 #16 PVC FRPVC	U500	25.5	GRAY	
5202UP 0091000	4 #16 PVC FRPVC	1000	51	WHITE	
5202UP 009500	4 #16 PVC FRPVC	500	27	WHITE	
5202UP 009U1000	4 #16 PVC FRPVC	U1000	51	WHITE	
5202UP 009U500	4 #16 PVC FRPVC	U500	25.5	WHITE	

**Detailed Specifications &
Technical Data**



5202UP Non-Paired - New Generation®

5202UP 0101000	4 #16 PVC FRPVC	1000	51	BLACK	C
5202UP 010500	4 #16 PVC FRPVC	500	27	BLACK	
5202UP 010U1000	4 #16 PVC FRPVC	U1000	51	BLACK	
5202UP 010U500	4 #16 PVC FRPVC	U500	25.5	BLACK	
5202UP D151000	4 #16 PVC FRPVC	1000	51	BLUE	
5202UP D15500	4 #16 PVC FRPVC	500	27	BLUE	C
5202UP D15U1000	4 #16 PVC FRPVC	U1000	51	BLUE	
5202UP D15U500	4 #16 PVC FRPVC	U500	25.5	BLUE	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 10-21-2004

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.