

**Detailed Specifications &
Technical Data**



573945 Coax - New Generation®

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--

Description:

Bare copper conductor, foam polyethylene insulation, bare copper braid shield. PVC jacket. Sequential footage marking every two feet.

SUITABLE APPLICATIONS:

Suitable Applications	Analog/Video CCTV
-----------------------	-------------------

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
RG Type	Mini 59/U
Series Type	Series 59
AWG	25
Stranding	Solid
Conductor Diameter	.018 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	Gas-injected FPE - Foam Polyethylene
Insulation Diameter	.085 in.

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	BC - Bare Copper
Outer Shield % Coverage	94 %

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.146 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-30°C To +75°C
UL Temperature Rating	75°C
Bulk Cable Weight	16 lbs/1000 ft.

Detailed Specifications & Technical Data



573945 Coax - New Generation®

Max. Recommended Pulling Tension	28 lbs.
Min. Bend Radius (Install)	1.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
NEC Articles	800
CEC/C(UL) Specification	CM

FLAME TEST:

UL Flame Test	UL1581 Vertical Tray
C(UL) Flame Test	FT1

SUITABILITY:

Suitability - Indoor	Yes - All colors
Suitability - Outdoor	Yes - Black only
Suitability - Burial	No

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	.109 µH/ft
Nom. Capacitance Conductor to Shield	16.9 pF/ft
Nominal Velocity of Propagation	80 %
Nominal Delay	1.27 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	31.0 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20°C	5.6 Ohms/1000 ft

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			.45
	5			.90
	10			1.3
	50			3.0
	100			4.1
	200			6.0
	400			8.6
	700			11.6
	900			13.5
	1000			14.5

Max. Operating Voltage - UL	300 V RMS
-----------------------------	-----------

**Detailed Specifications &
Technical Data**



573945 Coax - New Generation®

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
573945 001U1000	#25 GIFHDPE BRD PVC	U1000	16	BROWN	
573945 0021000	#25 GIFHDPE BRD PVC	1000	17	RED	C
573945 0041000	#25 GIFHDPE BRD PVC	1000	17	YELLOW	
573945 0051000	#25 GIFHDPE BRD PVC	1000	17	GREEN, DARK	C
573945 0061000	#25 GIFHDPE BRD PVC	1000	17	BLUE, LIGHT	C
573945 006U1000	#25 GIFHDPE BRD PVC	U1000	16	BLUE, LIGHT	
573945 0091000	#25 GIFHDPE BRD PVC	1000	17	WHITE	C
573945 0101000	#25 GIFHDPE BRD PVC	1000	17	BLACK	C
573945 010U1000	#25 GIFHDPE BRD PVC	U1000	16	BLACK	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 01-08-2004

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.