

Detailed Specifications & Technical Data



7988P Paired - Brilliance VideoTwist™ Enhanced Category 5e

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Color Code Chart : No. 8 for DataTwist Cables (Modified Western Electric).pdf</p>
---	---

Description:

4 Pair UTP, 24 AWG solid bare copper conductors, FEP insulation, bonded pairs, PVC Flamarrest® jacket, rip cord. Sequential marking at two foot intervals.

SUITABLE APPLICATIONS:

Suitable Applications Category 5e, UTP Based Video Applications, and KVM

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	Solid
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material FEP - Fluorinated Ethylene Propylene

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

OUTER SHIELD:

Outer Shield Material Unshielded

OUTER JACKET:

Outer Jacket Material Trade Name	Flamarrest®
Outer Jacket Material	LS PVC - Low Smoke Polyvinyl Chloride
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:

**Detailed Specifications &
Technical Data**



7988P Paired - Brilliance VideoTwist™ Enhanced Category 5e

Overall Nominal Diameter	0.193 in.
--------------------------	-----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
Bulk Cable Weight	29 lbs/1000 ft.
Max. Recommended Pulling Tension	40 lbs.
Min. Bend Radius (Install)	0.2 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMP
CEC/C(UL) Specification	CMP
IEC Specification	ISO11801 Category 5
TIA/EIA Specification	ANSI/TIA/EIA-568-B.2 Category 5e
Other Specification	NEMA WC-63.1 Category 5e, UL Verified to Category 5e

FLAME TEST:

UL Flame Test	UL910 Plenum
CSA Flame Test	FT6

PLENUM/NON-PLENUM:

Plenum (Y/N)	Y
Non-Plenum Number	7988R

ELECTRICAL CHARACTERISTICS:

Maximum Capacitance Unbalance (pF/100 m)	66 pF/100 m
Nominal Velocity of Propagation	72 %
Maximum Delay (ns/100 m)	510 ns/100 m
Typical Delay Skew (ns/100m)	9 ns/100 m
Maximum Conductor DC Resistance @ 20 Deg. C	9 Ohms/100 m
Maximum DCR Unbalance @ 20 Deg. C	3 %
Max. Operating Voltage - UL	300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals Table 1 :	
-------------------------------------	--

**Detailed Specifications &
Technical Data**



7988P Paired - Brilliance VideoTwist™ Enhanced Category 5e

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2.0	65.3	65.3	60.3	60.3	20.0	
4	4.1	56.3	53.3	49.2	49.2	23.0	
8	5.8	51.8	48.8	43.0	43.0	24.5	
10	6.5	50.3	47.3	40.8	40.8	25.0	
16	8.2	47.3	44.3	36.0	36.0	25.0	
20	9.3	45.8	42.8	33.5	33.5	25.0	
25	10.4	44.3	41.3	30.9	30.9	24.3	
31.25	11.7	42.9	39.9	28.2	28.2	23.6	
62.5	17.0	38.4	35.4	18.4	18.4	21.5	
100	22.0	35.3	32.3	10.3	10.3	20.1	
155	28.1	32.5	29.54	2.0	2.0	15.8	
200	32.4	30.8	27.8	1.0	1.0	15.0	

Premise Cable Electricals Table 2 :

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 15	100 ± 15	63.8	60.8
4	100 ± 15	100 ± 15	51.7	48.7
8	100 ± 15	100 ± 15	45.7	42.7
10	100 ± 15	100 ± 15	43.8	40.8
16	100 ± 15	100 ± 15	39.7	36.7
20	100 ± 15	100 ± 15	37.7	34.7
25	100 ± 15	100 ± 15	35.8	32.8
31.25	100 ± 15	100 ± 15	33.9	30.9
62.5	100 ± 15	100 ± 15	27.8	24.8
100	100 ± 15	100 ± 15	23.8	20.8
155	100 ± 25	100 ± 15	19.9	16.9
200	100 ± 25	100 ± 15	17.7	14.7

NOTES:

Notes US Patent #'s 5, 606, 151; 5, 734, 126. Electricals are preliminary, final data is pending.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
7988P N3UU1000	4 PR #24 FEP PVC	U1000	23	GREEN, MIL	
7988P N3UU1640	4 PR #24 FEP PVC	U1640	37.72	GREEN, MIL	

Revision Number: 2 Revision Date: 07-22-2004

**Detailed Specifications &
Technical Data**



7988P Paired - Brilliance VideoTwist™ Enhanced Category 5e

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.