


**Detailed Specifications &
Technical Data**



87760 Paired - Audio, Control, and Instrumentation Cable

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	---

Description:

18 AWG stranded (19x30) tinned copper conductors, twisted pair, FEP insulation, overall 100% Beldfoil® shield, 20 AWG stranded tinned copper drain wire, fluorocopolymer jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	18
Stranding	19x30
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material	FEP - Fluorinated Ethylene Propylene
Nom. Insulation Wall Thickness	.007 in.

Pair Color Code Chart :

Number	Color
1	Black & Red

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil® (Z-Fold®)
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	20
Outer Shield Drain Wire Stranding	Stranded
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:

Outer Jacket Material	PVDF - Fluorocopolymer
Outer Jacket Nominal Wall Thickness	.014 in.

OVERALL NOMINAL DIAMETER:

**Detailed Specifications &
Technical Data**



87760 Paired - Audio, Control, and Instrumentation Cable

Overall Nominal Diameter	.150 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +150°C
Bulk Cable Weight	22.6 lbs/1000 ft.
Max. Recommended Pulling Tension	64 lbs.
Min. Bend Radius (Install)	1.6 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMP
CEC/C(UL) Specification	CMP

FLAME TEST:

UL Flame Test	UL910 Steiner Tunnel
C(UL) Flame Test	FT6

PLENUM/NON-PLENUM:

Plenum (Y/N)	Y
Non-Plenum Number	8760

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	29 Ohms
Nom. Inductance	.15 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	51 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	97 pF/ft
Nominal Velocity of Propagation	69 %
Nominal Delay	1.47 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	5.5 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	7.3 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	5.4 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
87760 0021000	2#18 FEP FS SOLEF	1000	23	RED	C Z
87760 002500	2#18 FEP FS SOLEF	500	12	RED	C Z
87760 002U500	2 #18 FEP FS SOLEF	U500	12	RED	O

C = CRATE REEL PUT-UP.



87760 Paired - Audio, Control, and Instrumentation Cable

O = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 11-18-2003

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.