

EDV-PTZ4800N

Pan / Tilt / Zoom High Speed Dome Camera

Sacramento Electronic Supply
(800) 367-8800
sacramentoelectronics.com



Standard Features:

- 360° Continuous Pan Rotations
- 240° / sec Pan, 90° / sec Tilt
- Built-in OSD Function*
- Multiple RS-485 (RS-422) Protocol
DigiVue®, Pelco D, Panasonic, Kalatel and Sony
- Alarm Input and Output
- 64 Maximum Preset Position Programming*
- Maximum Connection 255

SPECIFICATIONS

MECHANICAL

Pan/Tilt Speed 0.8~240 per sec pan, 0.8~90 per sec tilt

Pan/Tilt Accuracy +/- 0.05Preset recalls

Pan Travel 360° Continuous rotation

Tilt Travel 0° Horizontal to 90° down

Dome Upper Cover Metal Aluminum

Dome Lower Cover Acrylic

Mounts Wall (included), Ceiling and pendant optional

Weight 4.5 lbs

FUNCTION

OSD 12 Characters*

Preset 64 Preset positions* (16 with DigiVue® software)

Signal System NTSC: 525 Lines

Image Sensor 1/4 inch interline Transfer SONY Super HAD CCD

Resolution Horizontal : 480 TV Lines

Video Output 1.0 Vp-p (75 Ohms, composite)

Lens 22x Optical Zoom (F1.6, f=3.9~85.8mm) Video AF

Digital Zoom 10x (Total Zoom Ratio: 220x), 2x ~ 10x Variable

Zoom Speed (Optical) 5.0 Sec

Angle Of View Horizontal : 47° (wide) / 3° (tele)

Min. Shooting Distance 1 cm (Wide) / 1 meter (Tele)

Min Illumination Day(1.0 lx), Night(0.001 lx, DSS)

Sync System Internal