



Elyssa Corporation

P.O. Box 138
Briarcliff Manor, NY 10510

EDV-XV425KIT

COMPLETE DIGITAL SECURITY VIDEO RECORDING SYSTEM

Featuring
DigiVue® with XView® Technology



Kit Contains:

(1) EDV-XV425

DigiVue® MPEG4 A/V DVR System with XView® Technology

- 60 FPS PER CARD
- MONITORS MULTIPLE IP ADDRESSES
- SUPPORT MULTI-RESOLUTION QCIF-VGA
- SUPPORTS MULTIPLE CARD INSTALLATIONS
- 20 VIDEO CHANNELS AND 1 AUDIO CHANNEL WITH 5 CARDS
- 4 CHANNEL VIDEO AND 1 CHANNEL AUDIO (WITH SOUND CARD)
- SUPPORTS REAL TIME LAN, WAN, AND INTERNET MONITORING: VIA LAN & ADSL AT REAL TIME IN 320X240, OR VIA PTSN (DIAL UP) AT 5-25 FPS IN QCIF

FEATURES:

- | | |
|--------------------|-----------------------------------------------------------------|
| • O.S. | WINDOWS XP / 2000* |
| • PASSWORD | SYSTEM / PLAYBACK / LOCAL AND REMOTE USERS |
| • PLAYBACK SPEED | FORWARD 2X, 4X, 6X, & 8X / BACK / STEP |
| • MOTION DETECTION | 16 ZONE X MULTIAREA FOR EACH CAMERA |
| • RECORD MODE | EVENT WITH PRE-ALARM / CONTINUOUS / SCHEDULE RECORDING |
| • DISPLAY SCREEN | 1 / 4 / 6 / 9 / 10 / 13 / 16 / 25 / 32 / FULL SCREEN |
| • RESOLUTION | 160X120 / 240X180 / 320X240 |
| • PTZ | RS422 / RS485 CONTROLLED PTZ AND LIGHT / POWER / WIPER |
| • MULTI-TASK | MONITORING / RECORDING / PTZ CONTROL / REMOTE / BACKUP |
| • WATER MARK | TIME WATER MARKING, NOT EDITABLE OR REPLACEABLE |
| • VIRTUAL MAPPING | SIMPLIFIED ACCESS THROUGH GRAPHIC REPRESENTATION OF SITE |
| • REMOTE CONTROL | FULL REMOTE FUNCTION AND REMOTE AUDIO TRANSMISSION |
| • COMPRESSION | SPECIAL MPEG4, FRAME SIZE: 1K~2.5K, 1200HR~4000HR / 80GB |
| • REMOTE RECORD | REMOTE PLAYBACK, REMOTE RECORDING AND EMERGENCY RECORDING |
| • COLOR ADJUSTMENT | ADJUSTABLE LIGHT, CONTRAST, HUE, SATURATION (INDIVIDUAL CAMERA) |
| • STORAGE | MULTIPLE HDD / VDRAM / CD-RW / DAT / MO / ZIP / RAID DRIVES |

(2) EC-624 Outdoor Color Day/Night Camera

- 1/4" CCD IMAGING CHIP
- OVER 30' IR RANGE
- 12VDC / 200MA OPERATION
- 0.1 LUX SENSITIVITY / 6MM F2.0 LENS
- 420 LINES RESOLUTION
- BUILT-IN ELECTRONIC IRIS CONTROL

This compact camera automatically switches from color to infrared sensitive black and white in low lighting conditions to provide a viewable image. With the included bracket, it is easily mountable indoors or out.

(2) ECMD-01 Micro Dome Color Camera

- CLEAR DOME
- 1.5CMOS IMAGING CHIP
- 12VDC / 100MA OPERATION
- CMOS IMAGING CHIP
- 380 LINES RESOLUTION
- SWIVEL AND PIVOTING CAMERA MOUNT INCLUDED

This miniature dome camera mounts on the wall or ceiling. It's contemporary styling and small size (2" X 2 1/4") makes it ideal for offices and other public spaces.

(4) EPS-12800 12VDC/800MA Regulated Power Supplies

(4) 50 FT Video / Power Cables

