


ATM Equivalent - Low Voltage Miniature Automotive, Fast Acting

Features

- Miniature Blade Type
- RoHS Compliant
- Available in Blister Package (B Suffix)



F-05



NTE Type No. (Note 1)	Rated Current	Color Code	Diag No.
74-MAF5A	5A	Tan	F-05
74-MAF7.5A	7.5A	Brown	F-05
74-MAF10A	10A	Red	F-05
74-MAF15A	15A	Blue	F-05
74-MAF20A	20A	Yellow	F-05
74-MAF25A	25A	Natural	F-05
74-MAF30A	30A	Green	F-05

Note 1. For blister package, add a "B" suffix.

Specifications

Rated Voltage: 32V

Time Current Characteristics:

% of Ampere Rating	Opening Time
110%	4 hours min.
135%	0.75 - 1800 seconds
200%	0.15 - 5 seconds
300%	0.08 seconds max.


ATC Equivalent - Low Voltage Automotive, Fast Acting

Features

- Fast Acting
- Clip, Hold Automotive Type
- RoHS Compliant
- Available in Blister Package (B Suffix)



F-06



NTE Type No. (Note 1)	Rated Current	Color Code	Diag No.
74-AF5A	5A	Tan	F-06
74-AF7.5A	7.5A	Brown	F-06
74-AF10A	10A	Red	F-06
74-AF15A	15A	Blue	F-06
74-AF20A	20A	Yellow	F-06
74-AF25A	25A	Natural	F-06
74-AF30A	30A	Green	F-06

Note 1. For blister package, add a "B" suffix.

Specifications

Rated Voltage: 32V

Time Current Characteristics:

% of Ampere Rating	Opening Time
110%	100 hours min.
135%	1800 seconds max.
200%	5 seconds max.
300%	0.08 seconds max.