

Part Numbers		Connector Type(s)	Cable Type(s)	Crimp Style or Type	Crimp Sizes	Connector Manufacturers or Remarks
Tool with Die	Die Only					
Coaxial Crimpers						
1609	2660	Coaxial, BNC/TNC, 3 Piece HDTV	BELDEN 8281 & 7505	HEX/SQUARE	0.324"/0.068" HEX & 0.042" SQ	KINGS, ADC, AMPHENOL HDTV
1611	2661	Coaxial, BNC/TNC, 3 Piece HDTV	RG59, BELDEN 1505A, BELDEN 8241	HEX/SQUARE	0.255"/0.068" HEX & 0.042" SQ.	KINGS, ADC, TROMPETER, AMPHENOL HDTV
1612	2662	Coaxial, BNC/TNC, 3 Piece HDTV	RG6, BELDEN 1694A, BELDEN 1855A	HEX/SQUARE	0.275"/0.178" HEX & 0.042" SQ.	KINGS HDTV
1613	2663	Coaxial, BNC/TNC, 3 Piece HDTV	BELDEN 1694A, NT735, BELDEN 8218	HEX/SQUARE	0.278"/0.197" HEX & 0.042" SQ.	ADC HDTV
1616	2003	Coaxial, BNC/TNC	RG174/RG179/RG188 and Small Cable Conn	HEX/SQUARE	0.178"/0.068" HEX & 0.042" SQ.	Crimps Pins, Ferrules, & Sleeve
1617	2005	Coaxial, BNC/TNC	RG58, RG59, RG62AU	HEX	0.255"/0.213"/0.068" HEX	Crimps Pins, Ferrules, & Sleeve
1619	2019	Coaxial, BNC/TNC	RG59, RG62AU, BELDEN 8281/8241	HEX	0.324"/0.255"/0.068" HEX	Crimps Pins, Ferrules, & Sleeve
NOTES: IF THE REQUIRED CRIMP STYLE AND DIMENSION IS NOT LISTED ABOVE, OR IF YOU ARE NOT SURE WHICH IS THE CORRECT CRIMP TOOL, DIVIDE THE CONNECTOR FERRULE OUTSIDE DIAMETER BY 1.155. IF THE RESULT IS WITHIN +/- 0.004 INCHES OF ANY OF OUR SIZES, THEN PICK OUR TOOL.						
Fiber Optic Crimpers						
1606	2044	Lucent Technologies SC Type	Fiber optic	HEX/ROUND	0.190" HEX/0.105" RND/0.090"RND	Lucent SC - Ferrules/Sleeves
1614	2664	SMA/SMB/FC/BICONIC FIBER	Fiber Optic	HEX	0.213"/0.178"/0.151"	SMA/FC/BICONIC FIBER
Insulated Terminal Crimpers						
1605*	NONE	Insulated Terminals and Lugs	Solid or Stranded Wire, 22-14 AWG	Terminal-Elliptical	16-14(Blu)/22-18(Red)	For Standard Commercial Terminals
1625*	NONE	Insulated Terminals and Lugs	Solid or Stranded Wire, 22-14 AWG	Terminal-Elliptical	16-14(Blu)/22-18(Red)	Amp Ultra-fast/Faston Terminals
Open Barrel Contacts and Terminals Crimpers						
1631*	NONE	Open Barrel Contact Pins	Solid or Stranded Wire, 24-14 AWG	F-Type	24-22/18-14	Molex/Waldom/Leoco Type Conn.
1645*	NONE	Open Barrel Contact Pins	Solid or Stranded Wire, 30-18 AWG	F-Type	30-24/22-18	Molex/Waldom/Leoco Type Conn.
NOTES: FOR THE ABOVE, THE PIN AWG SIZE MUST BE INSIDE THE RANGE OF THE CRIMP AREA AWG SIZE TO WORK. FOR EXAMPLE, IF THE AREA IS FOR 28-24 AWG, THE PIN MUST HAVE AN AWG RATING OF BETWEEN 28-24. NO SMALLER AND NO LARGER. EXAMPLE: 28-22 AWG RATED PIN WILL NOT WORK, IT IS TOO LARGE IN SIZE.						
Wire Ferrule Crimpers						
1647	2681	Insulated & Non-Insulated Ferrules	Solid or Stranded Wire, 20-10 AWG	TRAPEZOID	20-10	For DIN or US Type Wire Ferrules
1648*	NONE	Insulated & Non-Insulated Ferrules	Solid or Stranded Wire, 20-12 AWG	TRAPEZOID	20-12	For DIN or US Type Wire Ferrules

* The die sets for these tools are not removable or interchangeable. Removal of the die sets will void the warranty and cause the tool to lose calibration.