

VANDAL RESISTANT HIGH RESOLUTION COLOR, WALL/CEILING MOUNTABLE DOME CAMERA. Operates on 12V DC and 24VAC* with line lock and V-phase in 24 VAC mode

This fully tamper proof dome camera features a unique, internal 3-way bracket that allows either wall or ceiling mounting. It can be flush or surface mounted using the supplied surface mount adapter box. It is supplied with a tinted and clear "lined" dome to accommodate a wide range of lighting conditions. The safety strap holds the dome cover in place while making adjustments. It is conduit compatible and fits over a standard 2-gang box.



Specifications

Standard Resolution

Standard model **CVC-7WMTD**

Horiz. Resolution380 TV Lines
Image Device1/4" CCD Format
Min. Object Illumination1 lux
Effective Picture Element210 K
Backlight Comp. Active
Elec. Shutter1/60 - 1/100,000 second
Built-In Lens4mm, optional lenses available
Video S/N RatioGreater than 48dB
Weatherproof StandardIP67
Operating Environment-20 degrees F to 122 degrees F
TV FormatNTSC, color
Video Signal Output1.0Vp-p/75 Ohm (BNC)
Power Consumption110mA
Power Requirements12V DC reg. power supply (UL & CSA listing) included
Dimensions5-3/4" Dia. x 4" H
Weight3.2 lbs.

High Resolution

Variofocal **CVC-7WMTDV**

Horiz. Resolution480 TV Lines
Image Device1/3" Sony Super HAD** advanced image sensor
Min. Object Illumination0.03 lux
Effective Picture Element470 K
Backlight Comp. Active - Turbo
Elec. Shutter1/60 - 1/100,000 second
Built-In LensDC auto iris varifocal lens 4-9mm
Video S/N RatioGreater than 50dB
Weatherproof StandardIP67
Operating Environment-20 degrees F to 122 degrees F
TV FormatNTSC, color
Video Signal Output1.0Vp-p/75 Ohm (BNC)
Power Consumption200mA
Power Requirements24V AC @ 20 VA or 12V DC reg. power supply (UL & CSA listing) included
Dimensions5-3/4" Dia. x 4" H